O-LUBE

2/6/2017



1. PRODUCT AND COMPANY INDENTIFICATION

Product Name: O-Lube

Recommended Use: Lubricant (not for incidental food contact or medical purpose)

Company: Parker Hannifin

2360 Palumbo Drive Lexington, KY 40509

Telephone: 859-335-5101 **Emergency Telephone**: 859-269-2351

2. HAZARDS IDENTIFICATION

Classification: Category 5, Acute Toxicity – No Symbol

Labeling: Symbol: None

Signal Word: None

Hazard Statements

May be harmful if swallowed May cause eye irritation May cause skin irritation

Nonflammable or combustible, but may burn if involved in a fire

Precautionary Statements:

Use personal protective equipment as required. Wear safety glasses and

gloves.

3. COMPSOTION / INFORMATION ON INGREDIENTS

Chemical Identity: Barium, acetate tallow fatty acids complex; 10%-25%

Common Name: None 68201-19-4

This product contains no other hazardous components above reportable concentrations.

4. FIRST AID MEASURES

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get

medical attention.

O-LUBE

2/6/2017



Skin Contact: Was affected area with soap and water. If signs/symptoms persist, get

medical attention. No need for first aid is anticipated.

Inhalation: If signs/symptoms develop, remove person to fresh air. If signs/symptoms

persist, get medical attention.

Ingestion: If swallowed, do not induce vomiting. If irritation or discomfort occurs,

obtain medical assistance.

5. FIRE FIGHTING MEASURES

Flammable Limits (LEL) Not Determined Not Determined

Suitable Extinguishing Media: On large fires use dry chemicals, foam, or water spray. On

small fires use carbon dioxide, dry chemical, or water spray.

Water can be used to cool fire exposed containers.

Unsuitable Extinguishing Media: None

Specific hazards in case of fire: Decomposes on heating and produces incompletely burned

carbon compounds. Avoid reaction with oxidizers.

Special protective equipment and precautions for fire fighters:

No acute hazard. Move container from fire area if possible. Avoid breathing vapors or dusts. Keep upwind. Use full firefighting gear (bunker gear). Any supplied-air respirator with full face piece and operated in a pressure-demand or other positive pressure mode in combination with a separate escape air supply. Use any self-contained breathing apparatus with full face piece.

Alter fire brigade and indicate hazard location. Wear breathing apparatus plus protective clothing. Cool fire exposed containers with water spray from a protected location. Do not approach containers suspected to be hot. If safe to do so, remove containers from the path of the fire.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Not Required

Environmental Precautions: For larger spills, cover drains and build dikes to prevent entries into sewer systems or bodies of water. Collect the resulting residue containing solution. Place in metal container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

SAFETY DATA SHEET **O-LUBE**



2/6/2017

Methods for material containment and cleaning up: Observe precautions from other sections. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spill material as possible. Clean up residue with an appropriate solvent. Seal the container.

7. HANDLING AND STORAGE

Precautions for safe handling: No special measures required.

Conditions for safe storage, including any incompatibles: Store away from oxidizing

materials. Store product in a closed container located in a dry area. Do not store in open, inadequate, or mislabeled packaging. Check that containers are clearly labeled. Use metal cans, metal drums, plastic, or lined fiber containers. Keep away from heat and flame.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters: Under most handling conditions, this product will not generate mist or dust.

Components with limit values that require monitoring at the workplace:

64742-52-5 Distillates (petroleum), hydrotreated heavy naphthenic (50-100%)

ACGIH TLV Short-term value: 10mg/m³

Long-term value: 5mg/m³

OSHA PEL Long-term value: 5mg/m³

68201-19-4 Barium, acetate tallow fatty acids complex (10-25%)

ACGIH TLV Long-term value: 0.5mg/m³ OSHA PEL Long-term value: 0.5mg/m³

Additional Information: The lists were valid during the creation were used as basis.

9. CHEMICAL AND PHSYICAL PROPERTIES

Physical State: Semi-solid Amber colored Color: Odor: Mild. Petroleum like **Odor Threshold:** Not determined

O-LUBE

2/6/2017



pH Value: Not determined Melting Point: Undetermined

Freezing Point: Becomes very stiff with decreasing temperature around -20°C

Boiling Point: 370°C (698°F)
Flash Point: 190°C (374°F)
Evaporation Rate: Not available
Flammability: Not applicable
Ignition Temperature: >315°C (>599°F)
Explosion Limits: Not available
Vapor Pressure: Negligible at 20°C

Density: 0.9338g/cm³ (7.793 lbs/gal)

Vapor Density: Not available

Solubility in water: Not miscible or difficult to mix

Partition coefficient: Not available

Viscosity:

Dynamic: Not determined **Kinematic:** Not determined

Auto-ignition Temperature: Product is not self-igniting

Solvent Content:

Organic Solvent: 0.0% Solids Content: 20.0%

Decomposition temperature: Not determined

Danger of explosion: Product does not present an explosion hazard **Other information:** No further relevant information available

10. STABILITY AND REACTIVITY

Reactivity:

Chemical Stability: Stable under ambient temperatures and pressures.

Thermal decomposition/

conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions: No hazardous reactions have been identified.

Conditions to avoid: No specific conditions to avoid have been identified.

O-LUBE

2/6/2017

Materials to avoid: Oxidizers

Hazardous decomposition products: No dangerous decomposition products known.

-Parker

11. TOXICOLOGICAL INFORMATION

Acute Toxicity:

LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimates)

Oral LD50 2500mg/kg Inhalative LC50/4 h 55mg/l

68201-19-4 Barium, acetate tallow fatty acids complex

Oral LD50 500mg/kg (ATE) Inhalative LC50/4 h 11mg/I (ATE)

Primary irritant effect:

On the skin: No irritant effect.

Sensitization: No irritating effect.

Carcinogenic Categories:

IARC: None of the ingredients listed.

NTP: None of the ingredients listed.

OSHA-Ca: None of the ingredients listed.

12. ECOLOGICAL INFORMATION

Toxicity

Aquatic Toxicity:

Persistence and degradability:

Bio accumulative potential:

Mobility in soil:

No relevant information available.

No relevant information available.

No relevant information available.

General notes: Water hazard class 1 (Self-assessment): Slightly hazardous

in water. Do not allows undiluted product or large quantities

O-LUBE





of it to reach ground water, water course, or sewage

system.

PBT: Not available vPvB: Not available

Other adverse effects: No relevant information available.

13. DISPOSAL PROCEDURES

Waste treatment methods: Waste (substance and container material) shall be recycled/recovered or disposed of as applicable and in accordance with community (EU) and local legislation. Recycle wherever possible. Consult state land waste management authority for disposal. Bury at an approved site. Recycle containers if possible, or dispose of in an authorized landfill.

According to European Waste Catalogue, Waste codes are not product specific buy application specific. Waste codes should be assigned by the user based on the application in which the product is used.

For USA Disposal: Waste must be disposed of in accordance with federal, stae, and local environmental control regulations.

14. TRANSPORT INFORMATION

Class or Type: US DOT, IMO, ADR, RID, AND, IMDG, and IATA: Non-hazardous

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the mixture:

Other Information:

U.S. Regulatory Information

TSCO Inventory Status: Y

TSCA 12(b) Export Notification: Not listed

CERCLA Section 103 (40 CFR 302.4): N SARA Section 302 (40 CFR 355.30): N SARA Section 304 (40 CFR 355.40): N

SARA Section 313 (40 CFR 372.65): Barium compounds 68201-19-4

OSHA Process Safety (29 CFR 1910.119): N SARA Section 355 N

SARA Hazards Categories, SARA Sections 311/312 (40 CFR 370.21)-

Acute Hazard: N
Chronic Hazard: N
Fire Hazard: N

O-LUBE

2/6/2017



Reactivity Hazard: N Sudden Release Hazard: N

State Regulations: Not on California Prop 65 list. Does not contain any components known to the State of California to cause cancer or reproductive toxicity.

Carcinogenic categories:

EPA N TLV NIOSH-Ca N

16. OTHER INFORMATION

NFPA Hazard Classification:

Health: 1
Flammability: 1
Reactivity: 0
Special hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency personnel to address the hazards that are presented by short-term, acute exposure to material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIST Hazard Classification:

Health: 1 Flammability: 1 Reactivity: 0

Protection: B (See PPE Section)

Hazardous Material Identification System (HMIS) hazard ratings are designed to inform employees of chemical hazards in the workplace. The ratings are based on inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations.

These data are offered in good faith as typical values and not product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user

O-LUBE

2/6/2017



should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

Prepared By: Parker Hannifin

2360 Palumbo Drive Lexington KY 40509

Email: ordmailbox@parker.com

Phone: (859) 335-5101